

Specifications for: [OSOP Raspberry Shake](#) V4 / V5

- Your Personal Seismograph -
An IoT home automation device
Born on: October, 2016
<http://shop.raspberrysshake.org/>
sales@raspberrysshake.org
Last updated: 12-june-2017

Unit

The Raspberry Shake Personal Seismograph is an all-in-one, IoT plug-and-go solution for personal seismology- [OSOP, S.A.](#) integrates a vertical velocity sensor, the digitizer, the hyper damper, and the computer into *a single box*. The Raspberry Shake Personal Seismograph is manufactured in Volcán, Panamá using cutting-edge 3D printing and laser-cutting technology.

Warranty: 1 year from ship date

Specifications subject to change without notice.

Parameter	Value
Raspberry Shake Version	V4 / V5
Dimensions (estimated)	100x120x50 mm
Weight (estimated)	0.35 kg
Immersion rating	<i>Standard enclosure: IP10</i> <i>IP66 enclosure available upon request at additional cost</i>
Connectors	<i>Standard enclosure: Ethernet (RJ45), Power Micro USB (5V, 2.5 Amps), USB 2 ports x4, HDMI, Micro SD, CSI Camera port, Composite video and audio output jack</i>

	<i>IP66 enclosure: Ethernet (RJ45), Power</i>												
Installation Considerations	Designed for plug-and-go installation												
Operating Temperature	0 to 60 C (limited by RPi, the Raspberry Shake itself can go to -40C)												
On Board Computer	<p>Wifi-enabled Raspberry Pi 3 Model B</p> <p><i>The Raspberry Shake board/ Software is also compatible with:</i></p> <table> <tr> <td>000[d,e]:</td> <td>Model B</td> </tr> <tr> <td>00[10,13]:</td> <td>Model B+</td> </tr> <tr> <td>a[01040,01041,21041]:</td> <td>2 Model B</td> </tr> <tr> <td>9000[92,93],920093:</td> <td>Zero</td> </tr> <tr> <td>a[02082,22082,a32082]:</td> <td>3 Model B</td> </tr> <tr> <td>9000c1</td> <td>Zero W</td> </tr> </table>	000[d,e]:	Model B	00[10,13]:	Model B+	a[01040,01041,21041]:	2 Model B	9000[92,93],920093:	Zero	a[02082,22082,a32082]:	3 Model B	9000c1	Zero W
000[d,e]:	Model B												
00[10,13]:	Model B+												
a[01040,01041,21041]:	2 Model B												
9000[92,93],920093:	Zero												
a[02082,22082,a32082]:	3 Model B												
9000c1	Zero W												
Storage Device	<p>8 Gb or + micro SD card</p> <p><u><i>Est. # days of disk space:</i></u></p> <p>OS/ software: ~3 Gb</p> <p>Remaining space for data: ~5 Gb</p> <p># days (15 Mb/ day/ channel [x1]): ~330</p>												
Timing	Network Timing Protocol, NTP												
Timing Quality	NTP timing quality remains within 1 sample of accuracy versus startup accuracy: +/- 20 ms or better @ 50 sps												


Seismograph

Parameter	Value
Type	Single-component 4.5 Hz 395 Ohm vertical Racotech RGI-20DX geophone with electronic extension to lower frequencies (<1 Hz)
Samples per second	50
<p><i>Earthquake Early Warning (EEW) compatible*</i></p> <p><i>data packets shipped across serial port at a rate of 2 packets/ second (500 ms/ packet)</i></p>	
Flat Frequency Range (estimated, -3dB points)	0.8 to 23 Hz
Poles (estimated)	-6.75, 0, 0, 0
Zeros (estimated)	-4.21, -2.33, -1.30
Sensitivity (estimated)	4.69E+08 counts/ meter/ second +/- 10% precision
Clip Level (estimated)	+/- 8,388,608 counts (24-bits) 18 mm/s peak-to-peak from 0.1 to 10 Hz
Minimum Detection Threshold (estimate)	0.14 $\mu\text{m/s}$ RMS from 1 to 20 Hz @ 50 sps <i>Note: The minimum detectable level is considered to be 10dB above the noise RMS. Dynamic range is the full scale sinusoid RMS over the noise RMS in dB.</i>
Digitizer Dynamic range	24-bit ADC Sigma-Delta $\Sigma\Delta$ 144 dB (24 bits)

Effective bits (estimated)	<p>18.5 bits (110.5 dB) from 1 to 20 Hz @ 50 sps (for the entire analog to digital hardware chain).</p> <p><i>Note: Whereas most manufacturers report this for their digitizer only, we are reporting it for the entire sensor + ADC hardware chain. The effective bits of the digitizer itself are necessarily better.</i></p> <p>This parameter is also commonly known as “Dynamic Range” or “RMS to RMS noise”.</p>

**Applies to firmware versions 2.X.X and higher and units shipped purchased after July, 2017*

Velocity Channel Instrument Response:



Software

Software installed on Raspberry Shake's RPi computer
Native SeedLink Server (source: GEOFON) with OSOP Data Flow Message Router
Tight and automatic integration with SeisComP
Web-interface (HTML) for easy configuration
Software to store continuous seismic data in miniSEED format
Web-based helicorder plot generator (source: USGS)
Swarm (source: USGS)
Software distributed with Docker
Automatic updates
Operating System: Debian 8 (Linux)

Communications

Parameter	Value
Digital bandwidth consumption at 50 Hz, 1 channel (estimated)	Incoming rates RX: ~12.0 kbits/s Outgoing rates TX: ~47.0 kbits/s TCP Flow rate: 4.20 kbits/s
TCP/IP compatible	
Compatible with Wifi, Ethernet, Cell modem, GPRS, Satellite	

Power

Parameter	Value
Power Supply Voltage	5 Volts DC (2.5 Amp supply)
Power Consumption (RPi + Raspberry Shake, estimated)	5.14 Volts x 0.080 A = 0.4 Watts

Calibration Mechanism: Calibration not required over time but can be verified using the [OSOP Calibration Table](#). All sensors are verified prior to shipping to ensure that their gain is within <10% of the nominal instrument response.

Questions?

Email us at sales@raspberrysshake.org